


Deep Soil Mixing Design Minnick Road Section 14 Project



42nd Annual Southeastern Transportation Geotechnical
Engineering Conference, October 4-7, 2010, Charleston, WV



US Army Corps
of Engineers
Buffalo District

Jonathan E. Kolber, P.E.

Geotechnical Engineer



US Army Corps
of Engineers
Buffalo District

Introduction

The Minnick Road Section 14 Emergency Streambank Protection Project, located in the Town of Lockport, NY, exemplifies the application of deep soil mixing to stabilize a highway embankment along Tonawanda Creek, a tributary of the Niagara River




**US Army Corps
of Engineers**
Buffalo District

Location




US Army Corps
of Engineers
Buffalo District





**US Army Corps
of Engineers**
Buffalo District

Past Failures



LOCKWOOD LANE

MINNICK ROAD

BLOCK CHURCH ROAD SITE

SLOPE FAILURE (ADJACENT TO PRIVATE HOMEOWNER)

RIDDLE ROAD

BURDICK ROAD SITE

21 APRIL 2009 SLOPE FAILURE

1966 FAILURE

SITE #1

WEST PHALINGER SITE

SITE #2 BRAUER ROAD

HOPKINS ROAD

CAMPBELL ROAD

TONAWANDA CREEK ROAD

CURRENT PROJECTS

NO FEDERAL INTEREST

COMPLETED PROJECTS



US Army Corps
of Engineers
Buffalo District

Westphalinger Road Slide



06 27 2004 14:23



US Army Corps
of Engineers
Buffalo District

House Lost to Erosion Downstream of the Minnick Road Site





US Army Corps
of Engineers
Buffalo District

Minnick Road Site (Pre-Project)





US Army Corps
of Engineers
Buffalo District

Project History

- Problems first noted in the early 1990's
- Approved as a Section 14 project in 1999
- PCA executed in 2006
- Construction started in 2007
- Completed in 2008



US Army Corps
of Engineers
Buffalo District

Project Site Info

- Length 190 LF
- Bank height 25 feet
- 2 lane road
- Culvert through center of project with chronic seepage issues
- Settlement of guide rail and road on creek side (subtle progressive bank failure)



US Army Corps
of Engineers
Buffalo District

Local Geology

- Glacial deposits (Lake Tonawanda)
- Sand/silt layer overlies a thick (25+ feet) soft lacustrine clay layer
- Tonawanda Creek cuts through these layers
- Glacial till and bedrock underlie the soft clay layer
- The soft lacustrine clay layer is 30 to 50 feet below grade and governs slope stability in this region



US Army Corps
of Engineers
Buffalo District

Typical Stratification

Sand/Silt

Soft Clay

Glacial Till

Bedrock



US Army Corps
of Engineers
Buffalo District


Subsurface Explorations

- 1999 – 2 standard split spoon sample borings
- 2004 - 2 standard split spoon sample borings and 3 standard split spoon-undisturbed sample borings
- 2007 - 2 continuous standard split spoon sample borings and 2 continuous standard split spoon - undisturbed sample borings with field vane shear tests



US Army Corps
of Engineers
Buffalo District

Plan of Borings





US Army Corps
of Engineers
Buffalo District

Laboratory Soils Testing

- Natural moisture content
- Atterberg limits
- Grain size distribution
- UU triaxial
- CU triaxial
- UC and CU triaxial tests on soft clay mixed with cement (7, 14 and 28 day)



US Army Corps
of Engineers

Buffalo District

Geotechnical Parameters (Soft Clay)

- USCS classification: CL
- $LL=42$, $PL=22$, $PI=20$
- Natural moisture content 44%
- Average peak vane shear strength 255 psf
- Average remolded shear strength 66 psf
- Sensitivity 2.1 (moderately sensitive)



US Army Corps
of Engineers
Buffalo District

Soft Lacustrine Clay





**US Army Corps
of Engineers**
Buffalo District

Design



US Army Corps
of Engineers
Buffalo District

Remedial Design Options

- Modify the slope geometry
- Provide or improve surface and or subsurface drainage
- Provide internal slope strengthening/reinforcement
- Construct a retaining structure



US Army Corps
of Engineers
Buffalo District


Original Design – Steel Sheet Pile

- Steel sheet pile wall
- Front wall driven into glacial till
- Back wall shorter sheets
- Anchors in bedrock (about 60 feet below ground surface)
- Relatively disruptive to subsurface during construction



US Army Corps
of Engineers
Buffalo District

Initial Design Section – Anchored Sheet Pile Wall





US Army Corps
of Engineers
Buffalo District

Rationale for Design Change

- Vibrations from driving steel sheet pile wall might adversely affect existing utilities and several existing nearby houses on the opposite side of the road
- Vibrations could induce slope failure
- A/E firm had prior soil mixing design experience at a nearby slide site
- More cost effective than sheet pile wall



US Army Corps
of Engineers
Buffalo District

What is Dry Soil Mixing?

- 2 to 3 foot diameter columns
- Depths to 60 feet
- Suitable Soils:
 - Clayey Silt, Silty Clay, Clay, Sensitive Clay, Marine Clay, Organic Clay, Peat
- Soil mix column strength typically 10 to 50 times stronger and much stiffer than native soil



US Army Corps
of Engineers
Buffalo District

Soil Mixing Design

- Dry mix method
- 30 foot penetration of upper sands and lower soft clays into glacial till
- Soil-cement columns 30 inches in diameter
- 651 columns total, arranged into rows
- Average soil strength increased tenfold
- Slope stability FOS increased from 1.0 (existing case) to 1.5



US Army Corps
of Engineers
Buffalo District

Soil-Cement Mix Proportions

- 3 different mixes prepared and tested
- Type I Portland cement
- Cement content varied from 2.7% to 4% to 7.8% (8-10 94-lb bags per 30-foot column)
- Average 7 day compressive strength varied from 34 psi to 115 psi
- Average 14 day compressive strength varied from 49.5 psi to 140 psi



US Army Corps
of Engineers
Buffalo District

Dry Soil Mixing Procedure

- Mixing blade advanced through the entire thickness of the sand/silt and soft clay layers
- Cement injected under pressure as the blade is advanced back up
- High pore pressures induced (temporary)
- Rows of soil mixing holes alternated to minimize the effect of the high pore pressures
- Vibrating wire piezometers used on other nearby project to monitor pore pressures during mixing



US Army Corps
of Engineers
Buffalo District

Dry Soil Mixing

1. Positioning




2. Penetration



3. Completion of Penetration



4. Withdrawing Feeding Agent



5. Completion of Withdrawing




Column




US Army Corps
of Engineers
Buffalo District

Column Plan and Dry Mix Process

MINNICK ROAD SECTION 14 PROJECT DETAIL & PROCESS



COLUMN PLAN DETAIL



THE DRY-MIX DEEP SOIL PROCESS:

1. MIXING VANE IS ROTATED DOWNWARD THROUGH SOFT SOIL.
2. AT BOTTOM OF SOFT SOIL ZONE, VANE IS REVERSED AND MOVED UPWARD.
3. AS VANE ADVANCES UPWARD, DRY PORTLAND CEMENT IS INJECTED FROM PORTS IN VANE INTO SURROUNDING CYLINDER OF SOIL. THIS CEMENT HYDRATES NATURALLY, INCREASING THE STRENGTH OF IMPROVED SOIL CYLINDER.

Figure 3



US Army Corps
of Engineers
Buffalo District

Minnick Road Plan and Section




Figure 2



US Army Corps
of Engineers
Buffalo District

Cut Away View




Figure 1



US Army Corps
of Engineers
Buffalo District

Placing the Construction Pad





US Army Corps
of Engineers
Buffalo District

Casagrande B-135 Soil Mixing Rig





US Army Corps
of Engineers
Buffalo District

Cement Hopper





US Army Corps
of Engineers
Buffalo District

Soil Mixing Vane





US Army Corps
of Engineers
Buffalo District

Preparing to Advance the Vane





US Army Corps
of Engineers
Buffalo District

Vane Below Ground Surface





US Army Corps
of Engineers
Buffalo District

Performance Monitoring



US Army Corps
of Engineers
Buffalo District

3 Different QA Methods

- Shelby Tubes – dismissed due to difficulty and variability in results
- Continuous SPT Testing
- Vane Extraction Testing



US Army Corps
of Engineers
Buffalo District

Shelby Tube Sampling





US Army Corps
of Engineers
Buffalo District

SPT Sampling






US Army Corps
of Engineers
Buffalo District

Induced Pore Pressures

PLOT #1 - BORE HOLE 3-09
(23.5 foot depth)
(Logger # 08-21912)





US Army Corps
of Engineers
Buffalo District

Extraction Vane Assembly





US Army Corps
of Engineers
Buffalo District

Insertion of Extraction Vane





US Army Corps
of Engineers
Buffalo District


Uncovered Extraction Vane





US Army Corps
of Engineers
Buffalo District

Extraction Vane Results





US Army Corps
of Engineers
Buffalo District

Soil Improvement

- Initial Conditions (soft clay):
Shear strength = 100 to 300 psf
N-values (SPT) = Weight of Hammer
- Final Conditions (soil-cement columns):
Shear strength (design) 2000-3000 psf
Shear strength (vane extraction) 10,000 psf
N-values (SPT) = minimum 25 blows/ft



US Army Corps
of Engineers
Buffalo District

Time Line

- Project started in December 2007
- Completed in October 2008
- Equipment included Casagrande B-135 hydraulic piling rig – top 4 feet removed to compensate for this 40 ton live load
- Peak productivity 30 columns per work day under optimal conditions
- Productivity affected by obstructions in soil



US Army Corps
of Engineers
Buffalo District

Project Statistics

- The soil mixing volume measured 190 feet long by 40 feet wide by 26 feet deep (7320 CY)
- 651 30-inch diameter soil mix columns
- 38% of total volume was treated by mixing
- Minimum compressive strength of the completed columns 70 psi
- Total cost \$1.15 million



US Army Corps
of Engineers
Buffalo District

Selected Cost Information

- Anchored Sheet Pile Wall ~ \$2,100/LF
Estimated Total Cost = \$420,000 - \$440,000
- Dry Soil Mixing - \$15/LF of column
Total Cost = \$431,000
- Wet Soil Mixing - \$25-30/LF of column (w/o spoils removal)



US Army Corps
of Engineers
Buffalo District

Some Interesting Facts

- By miscalculation, twice the dosage of cement was used on this project than was planned, which turned out to be a blessing
- Large (2 feet) movements of the lower slope on the creek side occurred, due to the high induced pore pressures
- Obstructions along the culvert in the middle of the project, including boulders and concrete debris, forced a change in construction from soil mixing



US Army Corps
of Engineers
Buffalo District

Movement on the Creek Side





US Army Corps
of Engineers
Buffalo District

Obstructions Near Culvert





US Army Corps
of Engineers
Buffalo District

Damaged Mixing Vane





US Army Corps
of Engineers
Buffalo District

Some Unexpected Excitement

The job was shut down for one day mid-project when survey measurements indicated movement (several inches) along the other side of the road, where the utilities are located.



US Army Corps
of Engineers
Buffalo District

Survey Point that Moved





US Army Corps
of Engineers
Buffalo District

Problem Resolution

This turned out to be a survey bust as a result of a lawn mower hitting a survey stake. Everything returned to normal, but this sure caught a lot of attention for one day!



US Army Corps
of Engineers
Buffalo District

Completed Project





US Army Corps
of Engineers
Buffalo District

Completed Project





US Army Corps
of Engineers
Buffalo District

Acknowledgements

- Sophie Baj, Frank Lewandowski, and Shanon Chader, USACE, Buffalo District
- Mike Mann and Shawn Logan, McMahan and Mann Engineers, P.C.
- Mike Grant, Hayward Baker Inc.
- Dave Pastor, Nichols, Long and Moore Construction



US Army Corps
of Engineers
Buffalo District

Recognition

- Recipient of the 2008 Great Lakes and Ohio River Division Engineering Excellence Award for engineering excellence and technical innovation
- Nominated to the 2010 USACE Chief's Design and Environmental Awards



US Army Corps
of Engineers
Buffalo District

Lessons Learned

- Successful application of soil mixing to this small streambank protection project
- Likely applications to future nearby projects
- Soil mixing method dependent upon favorable subsurface conditions (soft clay, minimal obstructions, sufficient moisture for hydration of the cement)



US Army Corps
of Engineers
Buffalo District

Lessons Learned (Continued)

- When you try something new, you may have to overcome some old attitudes
- The best indicator of success came from a resident, who no longer felt the rumble of trucks driving past her house
- Teamwork led to success



US Army Corps
of Engineers
Buffalo District

Questions?

